

CE Test certificates for products issued in 2026

Certificate holder	Certificate No. / Properties	Product	Date of issue
MINJAE FLOOR CO., LTD. 10 Moo2 Thang Kwian Sub-District, Klaeng District RAYONG PROVINCE 21110 THAILAND	FLO-26-01-06-01 / Reaction to fire Formaldehyde emission Content of PCP	„Engineered Wood Floorings“, UV lacquered with following nominal dimensions: Top layer: Oak (3-6) mm, Core: Eucalyptus plywood, Back layer: Eucalyptus 1,2 mm Total length (350-2400) mm x Total width (60-300) mm x Total thickness (10-20) mm	6 January 2026
TOP WOOD SALES SRL 26 Roma Street, District 1, Bucharest, Romania	FLO-26-01-07-01 / Formaldehyde emission Content of PCP	Engineered wood flooring "Ro- bust Flooring" with different wood species in the top layer, UV lacquered, Core layer: Eucalyptus plywood, Back layer: Eucalyptus veneer Dimensions: length (300-3000) mm x width (45-300) mm x thick- ness (8-25) mm	7 January 2026
Muling Kemian Wood Industry Co., Ltd Xiachengzi Industry Park, Muling City, Mudanjiang City, Heilongjiang Province CHINA	FLO-26-01-09-01 / Formaldehyde emission Content of PCP	"Multiply Engineered Wood Flooring" with different wood species in the top layer, UV-lacquered top layer, Carrier board: Eucalyptus Plywood Length (400-2200) mm x Width (90-300) mm, Thickness range (14-20) mm	9 January 2026

CE Test certificates for products issued in 2026

Certificate holder	Certificate No. / Properties	Product	Date of issue
Muling Kemian Wood Industry Co., Ltd Xiachengzi Industry Park, Muling City, Mudanjiang City, Heilongjiang Province CHINA	FLO-26-01-09-02 / Formaldehyde emission Content of PCP	"3-layer parquet" with different wood species in the top layer, UV-lacquered top layer, Core: Poplar, Back layer: Poplar Length (400-2200) mm x Width (90-300) mm, Thickness range (14-15) mm	9 January 2026
Muling Kemian Wood Industry Co., Ltd Xiachengzi Industry Park, Muling City, Mudanjiang City, Heilongjiang Province CHINA	FLO-26-01-09-02 / Formaldehyde emission Content of PCP	"3-layer parquet" with different wood species in the top layer, UV-lacquered top layer, Core: Poplar, Back layer: Poplar Length (400-2200) mm x Width (90-300) mm, Thickness range (14-15) mm	9 January 2026
Ezzy Manufacturing Inc. dba Surface Vibe 283 W 154 st, South Holland IL 60473	FLO-26-01-15-01 / Reaction to fire Sliding behavior Formaldehyde emission	"Surface Vibe SPC Floorings", surface structure: "BP" Construction: UV coating layer, wear layer, decor layer, SPS core layer Dimensions: length (910-1524) mm x width (150-230) mm x thickness (4,0-7,0) mm	15 January 2026
Muling Kemian Wood Industry Co., Ltd Xiachengzi Industry Park, Muling City, Mudanjiang City, Heilongjiang Province, CHINA	FLO-26-01-26-01 / Reaction to fire Formaldehyde emission Content of PCP Anti-skid properties	"Multiply Engineered Wood Flooring", UV-lacquered, Surface structure: real wood, Top layer: Oak 3 mm, Back layer: (11,2 -17,2) mm Eucalyptus Plywood Length (400-2200) mm x Width (90-300) mm, Thickness range (14-20) mm	26 January 2026

CE Test certificates for products issued in 2026

Certificate holder	Certificate No. / Properties	Product	Date of issue
TONGXIANG XINYI IMPORT & EXPORT CO., LTD. NO.38 ZIJIN ROAD, PUYUAN TOWN, TONGXIANG CITY, JIAXING CITY, ZHEJIANG PROVINCE, CHINA	WCI-26-02-04-01 / Reaction to fire Migration of certain elements Vinyl chloride monomer (VCM)	"XINYi SPC Wall Covering", PVC top layer with UV-coating, Composition: Wear layer + Color film layer + SPC core layer Length (600-3200) mm x Width (300-1220) mm x Thickness (3,5-5,0) mm	4 February 2026
TONGXIANG XINYI IMPORT & EXPORT CO., LTD. NO.38 ZIJIN ROAD, PUYUAN TOWN, TONGXIANG CITY, JIAXING CITY, ZHEJIANG PROVINCE CHINA	FLO-26-02-04-02 / Reaction to fire Sliding behavior Formaldehyde emission	"XINYi LVT Flooring"; Composition: UV-coating, PVC wear layer (0,3 mm), colour film, LVT core; Name of the surface structure: "BP01" Dimensions: length (457-1530) mm x width (122-950) mm x thickness (2,0-5,0) mm	4 February 2026
TONGXIANG XINYI IMPORT & EXPORT CO., LTD. NO.38 ZIJIN ROAD, PUYUAN TOWN, TONGXIANG CITY, JIAXING CITY, ZHEJIANG PROVINCE CHINA	FLO-26-02-04-03 / Reaction to fire Sliding behavior Formaldehyde emission	"XINYi SPC Wall Covering"; Composition: UV-coating, PVC wear layer (0,3 mm), colour film, SPC core; Name of the surface structure: "BPQ" Dimensions: length (457-1850) mm x width (122-950) mm x thickness (3,5-8,0) mm	4 February 2026
Jiangsu Zhengyoung Flooring Decoration Material Co.,Ltd. No. 32 Cuibei Village, Henglin Town, Wujin District, Changzhou City, Jiangsu Province, Postcode 213101, CHINA	FLO-26-02-04-03 / Formaldehyde emission	PVC Flooring/LVT Flooring Composition: UV-coating, PVC-wear layer, colourfilm layer, LVT-composite layer Dimensions: length (100-2000) mm x width (100-610) mm x thickness (2,0-6,0) mm	11 February 2026

CE Test certificates for products issued in 2026

Certificate holder	Certificate No. / Properties	Product	Date of issue
Homello Group Sp. z o.o. sp. k. Buszewo 10, 62-045 Pniewy, Polska, NIP: PL7872103795	FLO-26-02-12-01 / Reaction to fire Sliding behavior Formaldehyde emission	"SPC Floorings Homello Group" Top layer: UV lacquered PVC with surface structure "BP" or "EIR" Dimensions: length (450-1830) mm x width (83-610) mm x thick- ness (3,2-8,0) mm	12 February 2026
Jiangsu Zhengyoung Flooring Decoration Ma- terial Co.,Ltd. No. 32 Cuibei Village, Henglin Town, Wujin District, Changzhou City, Jiangsu Province, Postcode 213101, CHINA	FLO-26-02-13-01 / Reaction to fire Sliding behavior Formaldehyde emission	PVC Flooring/LVT Flooring UV-coated wear layer with 2 dif- ferent surface embosses, colourfilm, LVT-composite layer Dimensions: length (100-2000) mm x width (100-610) mm x thickness (2,0-6,0) mm	13 February 2026
Homello Group Sp. z o.o. sp. k. Buszewo 10, 62-045 Pniewy, Polska, NIP: PL7872103795	FLO-26-02-13-02 / Reaction to fire Sliding behavior Formaldehyde emission	"PVC Flooring/LVT Flooring Homello Group" UV-coated wear layer with 2 dif- ferent surface embosses, colourfilm, LVT-composite layer Dimensions: length (100-2000) mm x width (100-610) mm x thickness (2,0-6,0) mm	13 February 2026